



## Handwheel Operated Water Control Valve On Off Type For Sewage Water System

### Our Product Introduction

#### Basic Information

- Place of Origin: China
- Brand Name: OEM
- Certification: EN1074-2, ISO9001
- Model Number: GBBX, GBHX, GBCX
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Plywood Cases
- Delivery Time: 15-60 Days
- Payment Terms: L/C, T/T
- Supply Ability: Based On Order



#### Product Specification

- Material: Ductile Iron
- Standard: EN1074-2, BS5163
- Color: Blue RAL5010
- Rubber: WRAS Approved EPDM
- Stainless Steel: SS420, SS431
- Media: Water, Sewage Water
- Highlight: **water pressure valve**

for more products please visit us on [watercontrol-valve.com](http://watercontrol-valve.com)

## Product Description

### Handwheel Operated AFC Resilient Seated Gate Valve On Off Type

#### Forming Machine Process

1. CNC Lathe Processing
2. High precision CNC machining center processing
3. General lathe processing
4. The machine punch the product parts
5. Cold Forming Molding
6. Welding Assembly

#### Features:

- Body & bonnet are made of high grade ductile Iron GJS500-7
- Disc is designed with an abrasion resistant nylon guide which can help less opening or closing torque and smooth during operation.
  1. EPDM fully vulcanized
  2. WRAS approved
- Forged stem provide stronger stem operation and less moving parts.
  1. SS420 / 431
  2. Platform provide better strength
- Disc is covered by high-grade rubber which complies with drinking water.
- High-tech rubber curing with precise geometry dimensions, more resilient & strong adhesive to ductile casting.
- The 4 O-ring stem seals are designed to prevent stem leakage. and provide replacement of the O-ring without disassembling of valve from mainline pipes.
- Both inside & outside are coated with epoxy resin powder.
- Manufacturing standard meets BS EN 1074-1, EN1074-2, BS 5163, BS EN 1171.
- F/F (Face to Face) meets the following standard: BS EN558-1.
- Bolts are protected by silicon glue.

Size	DN50-DN600
Working Temperature	- 10 C- 80 C
Flange	PN10/16
Flow Media	Water, Sewage Water
Face to Face	EN558-1

#### Material:

Valve Body	DI GJS500-7
Valve Bonnet	DI GJS500-7
Valve Gland	DI GJS500-7
Wedge	DI GJS500-7 with fully vulcanized EPDM
Stem	SS420/SS431
Stem nut	Brass/Bronze
O-ring	NBR



Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



[miclecleanmo@gmail.com](mailto:miclecleanmo@gmail.com)



[watercontrol-valve.com](http://watercontrol-valve.com)

18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.