



Welded / Tri Clamp / Threaded Butterfly Valve Stainless Steel 304 316L Made

Our Product Introduction

for more products please visit us on watercontrol-valve.com

Basic Information

- Place of Origin: China
- Brand Name: OEM
- Certification: CE, 3A, ISO9001, FDA, BPE
- Model Number: CX-SBTY-005
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Plywood Cases
- Delivery Time: 15-60 Days
- Payment Terms: L/C, T/T
- Supply Ability: Based On Order



Product Specification

- Operated By: Stainless Steel Pneumatic Actuator
- Control Mode: Remote Control, By Intelligent Automation Control Unit
- Connection Options: Butt Weld, Thread, Tri Clamp, Flange
- Connection Standard: DIN, ISO, IDF, 3A, ASME BPE, SMS
- Port Size: DN25-DN200; 1" ~ 8"
- Application: Production Pipelines Of Food, Pharmacy, Water, Dairy, Beverage, Wine, Chemical Fluid
- Highlight: **stainless steel butterfly valve**



More Images



Product Description

Hygienic Sanitary Stainless Steel SS304/SS316L Manual & Pneumatic Welded / Tri Clamped / Threaded Butterfly Valves

Our company is specialist in design and production of high quality water valve, and has grown to become one of the leading manufacturers for fluid control valve. We design and manufacture a wide range of fluid valve, such as float control valve, trunnion ball valve, water pressure reducing valve, rotary airlock valve, sanitary butterfly valve, hydraulic check valve, sewage air release valve, etc. Our constant technical innovation combined with stringent quality control systems has enabled us to deliver high performance and outstanding value in industrial applications.

Characteristics:

A higher class pneumatically actuated butterfly valve
Hygienic design for food, beverage, pharmacy and biotechnology industries
Automatically controlled by an intelligent control unit
Easy installation and self-configuration
Can be easily switched from normally open to normally closed mode
7 / 24 visible indication
Convenient for daily maintenance and repair

Main Parts:

1. Intelligent Automation Control Unit: precise surveillance, remote control
2. Pneumatic Actuator: made of stainless steel, strong and easy setup
3. Hanger: stainless steel, to hold actuator and control unit
4. Butterfly Valve: 304 or 316L material, simple and compact configuration design



Working Principle:

1. Push the button of blue automation control unit, and run the pneumatic actuator
2. The pneumatic actuator can be spring return design or double air acting design
3. The operation of pneumatic actuator moves its piston to rotate the valve stem by 90 degrees
4. Valve is opened or closed accordingly to control medium flow rate of the pipeline

Specifications:

Valve Body Material:	SS304 or SS316L, forged, material inspection report available
Seal Material:	Optional from Silicon, EPDM, PTFE, Viton, NBR
Size:	1"-8" or DN25-DN200
Operating Type:	Pneumatic actuator with double acting (NO or NC) or spring return
Control Mode:	Precise automation control unit
Connection ends:	Weld, Clamp, Male or Female thread, Flange
Inside Surface Treatment:	Ra≥0.4-0.8 um
Surface Treatment:	Ra≥0.8-1.6 um
Working Temperature:	-20 degree to +120 degree (EPDM)
Working Pressure:	Max. 10 Bar
Air Supply Pressure:	5 - 8 Bar



Food



Dairy



Beverage



Pharmacy



Beer



Drinks



Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



watercontrol-valve.com

18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.