



## Reliable Sanitary Butterfly Valve , Stainless Steel 304 316L Flanged Butterfly Valve

Our Product Introduction

for more products please visit us on [watercontrol-valve.com](http://watercontrol-valve.com)

### Basic Information

- Place of Origin: China
- Brand Name: OEM
- Certification: CE, ISO9001, 3A, FDA
- Model Number: CX-SFBV-01
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Plywood Cases
- Delivery Time: 15-60 Days
- Payment Terms: L/C, T/T
- Supply Ability: Based On Order



### Product Specification

- Operation: Pull Rod Handle, 4 Gears
- Diameter: DN 15 - DN200, 1/2" - 6", Or Custom On Request
- Working Pressure: 0-10 Bar
- Connection Ends: Flanged
- Seal Material: Silicone, EPDM, Viton, NBR
- Application: Pipe Lines In Hygienic Industries Like Food, Pharmacy, Dairy, Beverage, Breweries
- Highlight: **stainless steel butterfly valve**



### More Images



## Product Description

### Stainless Steel 304,316L Material Sanitary Flanged Butterfly Valve with Pull Handle

#### Surface Treatment

We offer the following processes to choose:

1. Mechanical Polishing (MP) to improve brightness (gloss, matte)
2. Acid Cleaning for Anti-corrosion
3. Electrolysis Polish (EP) to improve surface smoothness
4. Custom Process: Bright Annealing treatment eliminate stresses to improve toughness

#### Characteristics:

All parts are frilled to comply with DIN and ANSI side connection  
 Strong stainless steel handle, perfect function with good looking appearance  
 High precision valve disc edge brings double tightness  
 Low torque, long lifetime of valve seat  
 EPDM seal can withstands wide temperature range -20 ~ +150 degrees

#### Highlights of flange connection end:

Suitable for all kinds of pipelines with different sizes and pressure  
 Very firm and strong connection to the pipeline  
 Safe and reliable  
 Can easily remove and replace any time  
 Very convenient for daily repair and maintenance

#### Our Competitive Advantages:

Over 20 years manufacturing experience in sanitary valve&fittings field.  
 No requirement on MOQ, sample order accepted  
 OEM or customization accepted  
 Strict quality control system including complete set of testing and inspections  
 Inventory of most standard models for fast delivery service  
 All products are inspected before shipment

#### Specifications:

Port Size	DN15-DN200 , 1/2" - 8" , or custom on request
Operation Mode	Manual handle
Raw Material	Body: SUS304, SUS316L forged Gasket: EPDM, PTFE, etc.
Working Temperature	-10 to +100 degrees centigrade
Working Pressure	Up to 10 bar
Connection Ends	Clamp, flange, union, thread, butt weld or on request
Dimension Standard	ISO, DIN, IDF, 3A, SMS etc.
Medium	Beer, red Wine
Surface Treatment	Mirror Polish

#### Product Show:



Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



[miclecleanmo@gmail.com](mailto:miclecleanmo@gmail.com)



[watercontrol-valve.com](http://watercontrol-valve.com)

18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.