



Basic Information

Place of Origin: ChinaBrand Name: OEM

Certification: CE, ISO9001Model Number: CX-SBTY-001

Minimum Order Quantity:

Price: Negotiable
Packaging Details: Plywood Cases
Delivery Time: 15-60 Days
Payment Terms: L/C, T/T

Supply Ability: Based On Order



Product Specification

• Pressure: Low Pressure

• Temperature Of Media: Medium Temperature

Application: GeneralShape: RoundStructure: Butterfly

Material: Stainless Steel3304/316L

Port Size: StandardType: Butterfly Valves

Power: Pneumatic Actuator, Handle Operated

• Highlight: stainless steel butterfly valve



More Images





Product Description

Hygienic Sanitary Stainless Steel 304,316L welding type Butterfly Valve with Pneumatic Actuator

About us

Our company is specialist in design and production of high quality water valve, and has grown to become one of the leading manufacturers for fluid control valve. We design and manufacture a wide range of fluid valve,, such as float control valve, trunnion ball valve, water pressure reducing valve, rotary airlock valve, sanitary butterfly valve, hydraulic check valve, sewage air release valve, etc. Our constant technical innovation combined with stringent quality control systems has enabled us to deliver high performance and outstanding value in industrial applications.

Technical Specifications

Valve Body Material:	1.4404/1.4301, SS304/SS316L
Seal Material:	EPDM (standard) FPM/SILICON/NBR, FDA177.2600
Mex working pressure:	10Bar
Max. Working Temperature:	-10 °C to120 °C(EPDM Seal)
Availably size:	DN25-DN100, 1"-4"
Availably connection:	Clamp / weld / thread/ weld thread/ flange
Availably standard:	3A/DIN/SMS/RJT/ISO/IDF
Operated:	Manual, Pneumatic, Electric
Control:	Sensor, C-TOP, C-top controller(AS-I)
Certificate:	ISO, PED/97/23/EC, FDA.177.2600
Handle application:	Two-position handle, three-position handle, four-position pull handle, multi-position plastic handle and multi-position stainless steel handle
Application scope:	Dairy,food, beverage, pharmacy, cosmetic, Chemical, etc
Packaging Details:	Bubble pack for each valve. Outside packing are carton or plywood cases. Or as per the request of customers.
Delivery details:	Usually within 20 days after receiving T/T down payment.

Operating principles

The butterfly valves can be operated automatically through actuator or manually with the handle. The handle blocks the valve in the "open" or "closed" position, certainly there are the other position available. The actuator push piston of axial movement into 90 degree so that it controls butterfly vavle.

For more detail information or catalog pls don't hesitate to contact us. We can also produce according to your drawings and specifictions.



Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



watercontrol-valve.com

18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.