



Low Pressure Stainless Steel Butterfly Valve , Pneumatic Operated Butterfly Valve

Our Product Introduction

for more products please visit us on watercontrol-valve.com

Basic Information

- Place of Origin: China
- Brand Name: OEM
- Certification: CE, ISO9001
- Model Number: CX-SBTY-002
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Plywood Cases
- Delivery Time: 15-60 Days
- Payment Terms: L/C, T/T
- Supply Ability: Based On Order



Product Specification

- Pressure: Low Pressure
- Temperature Of Media: Medium Temperature
- Application: General
- Shape: Round
- Structure: Butterfly
- Material: Stainless Steel3304/316L
- Port Size: Standard
- Type: Butterfly Valves
- Power: Pneumatic Actuator,Handle Operated
- Name: Stainless Steel Butterfly Valve
- Highlight: **stainless steel butterfly valve**



More Images



Product Description

Stainless Steel Hygienic Food Grade Pneumatic Actuator Welding type Butterfly Valve

How do we control the quality of machining

1. High-precision CNC lathe processing parts.
2. Advanced Milling Machines
3. UT Inspection to ensure welding quality
4. Weld Polishing
5. 100% Appearance & Size Inspection online (thickness, roundness, etc.)
6. Size & Appearance Shaping

Technical Specifications

Valve Body Material:	1.4404/1.4301, SS304/SS316L
Seal Material:	EPDM (standard) FPM/SILICON/NBR, FDA177.2600
Max working pressure:	10Bar
Max. Working Temperature:	-10 °C to 120 °C (EPDM Seal)
Available size:	DN25-DN100, 1"-4"
Available connection:	Clamp / weld / thread / weld thread / flange
Available standard:	3A/DIN/SMS/RJT/ISO/IDF
Operated:	Manual, Pneumatic, Electric
Control:	Sensor, C-TOP, C-top controller (AS-I)
Certificate:	ISO, PED/97/23/EC, FDA.177.2600
Handle application:	Two-position handle, three-position handle, four-position pull handle, multi-position plastic handle and multi-position stainless steel handle
Application scope:	Dairy, food, beverage, pharmacy, cosmetic, Chemical, etc
Packaging Details:	Bubble pack for each valve. Outside packing are carton or plywood cases. Or as per the request of customers.
Delivery details:	Usually within 20 days after receiving T/T down payment.

Operating principles

The butterfly valves can be operated automatically through actuator or manually with the handle.
 The handle blocks the valve in the "open" or "closed" position, certainly there are the other position available.
 The actuator push piston of axial movement into 90 degree so that it controls butterfly valve.



Beijing Silk Road Enterprise Management Services Co., LTD



17733330123



miclecleanmo@gmail.com



watercontrol-valve.com

18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.