



## Fire Safe Design Trunnion Ball Valve Casted Carbon Steel / Stainless Steel Made

### Our Product Introduction

#### Basic Information

- Place of Origin: China
- Brand Name: OEM
- Certification: API, ISO, CE, GOST, TS, BS1873, BS5351, API 6D, 600, 602, 609, ASME B16.34, API 6FA, API607 etc
- Model Number: 2"-24", CL150-2500
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Plywood Cases
- Delivery Time: 15-60 Days
- Payment Terms: L/C, T/T
- Supply Ability: Based On Order



#### Product Specification

- Size: NPS 2"~24"
- Pressure Rating: Class 150~2500
- Material: WCB, LCC, LCB, 4A, 5A Etc
- Design & Manufacturing Standard: API 6A, API 6D, API 6DSS, BS 5351, ASME B16.34
- Face To Face: ASME B16.10, API 6D
- End Connection: ASME B16.5, ASME B16.47, ASME B16.25
- Test And Inspection: ISO 5208, API 6D, API598
- Operation Method: Manual, Worm Gear, Electric Actuator, Pneumatic Actuator
- Highlight: trunnion mounted ball valve



## Product Description

**Trunnion ball valve of 2"-24" CL150-2500 casted Carbon steel, Stainless steel**

### How do we ensure finished product quality (FQC inspection)

1. Visual Inspection
2. Material Grade Measurement
3. Dimension Inspection
4. Roughness Detection
5. Roughness Detection
6. Leakage Test

The Cast Trunnion Mounted Ball Valve's split body construction complies with API 6D, ASME B16.34, API 608, API 607 and other relevant ASTM specifications. With a variety of material selections available as well as ISO 5211 complaint direct mount actuator pad, the Cast Trunnion Ball Valve can be customized and automated to suit a complete range of oil and gas applications.

Sizes 2" to 24", ASME Class 150 through 2500

API 6D Monogrammed, ISO 14313, CSA Z245.15-17

NACE MR0175/ISO 15156-1

Material Traceability to ASME B31.1

Compliant with ASME B16.5, B16.10 and ISO 52115

PED 2014/68/EU Annex III, Module H

Fire Safe: API 607 7th Edition

Product type	Casting trunnion ball valves	
Product description	2-PC/3-PC Side-entry Trunnion Mounted Ball Valve	
Model	Q47F/H	
Size	NPS 2" 24"	
Seal type	Soft Seal	Metal to Metal
Operating temperature	-46°C 121°C	-46°C 593°C
	ACC to material	ACC to material
Operating pressure	CLASS 150 CLASS 2500	CLASS 150 CLASS 2500
Material	WCB,LCB,CF8,CF8M,CF3,CF3M,CN7M .etc	
Standard	API 6D,API 608,BS5351,ISO 17292	
Face to face	ASME B16.10	
Connecting end	ASME B16.5,ASME B16.47,ASME B16.25	
Test standard	API 598,API 6D,ISO 5208	
Operation	manual, electric, hydraulic, pneumatic, gas over oil, electric over oil actuators	
Application fields	water, Oil, natural gas, CNG	
Function	DBB	
Other remark 1	Fire proofing and antistatic design	
Other remark 2	Injection system	
Other remark 3	Valve stem fly out prevention structure design, to prevent accident due to fly out of valve stem caused by abnormal pressurization in the pipeline	



**Beijing Silk Road Enterprise Management Services Co.,LTD**



17733330123



miclecleanmo@gmail.com



watercontrol-valve.com

18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.