



Gear Operation Fully Welded Ball Valve NPS 6" - 36" With Long Lifespan

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: OEM
- Certification: API, ISO, CE, GOST, TS, BS1873, BS5351, API 6D, 600, 602, 609, ASME B16.34, API 6FA, API607 etc
- Model Number: 6"-36", CL150-600
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Plywood Cases
- Delivery Time: 15-60 Days
- Payment Terms: L/C, T/T
- Supply Ability: Based On Order



Product Specification

- Size: NPS 6"~36"
- Pressure Rating: Class 150~600
- Material: A105, LF2, F304, F316, F304L, A106-B, 20# Etc
- Design & Manufacturing Standard: API 6D, KS, BS 5351, ASME B16.34
- Face To Face: ASME B16.10, API 6D
- End Connection: ASME B16.5, ASME B16.47, ASME B16.25
- Test And Inspection: ISO 5208, API 6D, API598
- Operation Method: Manual, Worm Gear, Electric Actuator, Pneumatic Actuator
- Highlight: **soft seated ball valve**

Product Description

Fully welded ball valve, BW flange with gear operation, 6"-36"

Fully welded ball valve features:

Since the all-welded ball valve body is welded, the valve is light and easy to insulate.

The spring-loaded PTFE sphere seal ensures absolute tightness under all application conditions

All welded ball valve ball and stem are made of stainless steel with two o-ring anti-flying valve stem structure to ensure the tightness, the upper container can be replaced, the working life is long

All welded ball valves are available in welded, wired and flanged versions

Obtained ISO 9001 certification

Steel ball valves are suitable for use in local heating and cooling systems, pressure gas lines and oil lines.

Fully welded flanged floating ball valves from series 6"-36" utilize flange connecting method to make them compatible with other flange-connected products. The valve replacement process is rather convenient. These kinds of valves are suitable for pipeline branches, underground pipeline, gas delivery equipment, liquid storage device, tunnel construction, etc.

Valve opening: flat steel handle (standard configuration)/worm wheel (optional configuration); motor driven/pneumatically driven/hydraulic driven (optional configuration)

Medium: water, oil, gas

Product introduction

All welded ball valve material:

1): Valve body: carbon steel, A106-B; No. 20 steel

2): Sphere: Stainless steel 304 or 316

3): Stem: 2Cr13

4): stem seal: perfluoro-like glue

5): Sphere seal: PTFE (PTFE + C)

Standard features of all welded ball valves:

1): Size: DN150 900

2): Pressure: PN 16 64

3): Working temperature: -29 °C ~ +200 °C

4): All welded ball valve adapts to medium: water, oil, natural gas

5): All-welded ball valve operation mode: water, oil, natural gas

We are committed to offering products that meet a wide range of applications and requirements. We continually improve our product line by introducing new products and enhancing existing designs. Providing our customers with the best quality in the market.



Beijing Silk Road Enterprise Management Services Co., LTD



17733330123



micleanmo@gmail.com



watercontrol-valve.com

18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.