



3 - Point Control Electric Actuated Ball Valve G Standard OEM Acceptable

Our Product Introduction

for more products please visit us on watercontrol-valve.com

Basic Information

- Place of Origin: China
- Brand Name: OEM
- Certification: CE
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Plywood Cases
- Delivery Time: 15-60 Days
- Payment Terms: L/C, T/T
- Supply Ability: Based On Order



Product Specification

- After-sales Service Provided: Online Support
- Warranty: 18 Month
- Certificate: CE, RoHS
- Temperature Of Medium: 2°C...90°C
- Rated Pressure: PN16
- Pipe Connector: Internal Thread
- Flow Characteristic: Equal Percentage, On/off
- Valve Body: Forged Brass, Hpb59-1
- Seal Ball: EPDM+PTFE
- Name: Water Flow Electric Control Valve
- OEM: Acceptable
- Warranty: 18 Months
- Port: Changsha
- Highlight: electrically operated valve



More Images



Product Description

G standard 3~point control water flow control valve

Abut us

Our company is specialist in design and production of high quality water valve, and has grown to become one of the leading manufacturers for fluid control valve. We design and manufacture a wide range of fluid valve,, such as float control valve, trunnion ball valve, water pressure reducing valve, rotary airlock valve, sanitary butterfly valve, hydraulic check valve,sewage air release valve, etc. Our constant technical innovation combined with stringent quality control systems has enabled us to deliver high performance and outstanding value in industrial applications.

Actuator

WVA4-2... 24VAC/DC±15%,3-point

Function (3-point,or proportional type)

The actuator is controlled by a modulating on/off, 3-point, and proportional control signal, using high transmitting ratio gear drive to fix and lock.

Brown wire is power on ,counterclockwise rotation, valve open

Red wire is power on,clockwise rotation, valve close

Brown or red wire is power off ,Valve keep the current position

Matching Valve body parameters:

Model No.	Working Voltage	Actuator type	Output torque	Consumption	Valve body
WVA4-304	24VAC/DC±15% %	3-point	0-10V	6VA	DN25,DN20,DN15
WVA4-306			0(2)-10VDC&(0)4-20mA		DN50,DN40,DN32,
WVA4-310			0(2)-10VDC&(0)4-20mA		DN50

Model No	Commodity	Application	Actuator	Valve body	Spindle
WCBV-1	Connector	Be used to connect the actuator and the valve body	WVA4-106,WVA4-206 WVA4-306,WVA4-110 WVA4-210,WVA4-310	WCBV232 WCBV240	WCBV-2
WCBS-1			WVA4-104,WVA4-204 WVA4-304,WVA4-106 WVA4-206,WVA4-306 WVA4-110,WVA4-210 WVA4-310	WCBS232,WCBS240 WCBS250,WCBS332 WCBS340,WCBS350	WCBS-2 WCBS-3

Product Description



Production Process





Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



micleanmo@gmail.com



watercontrol-valve.com

18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.