

# High Performance Electric Actuated Ball Valve , 2 Way Motorised Valve

# Basic Information

Place of Origin: ChinaBrand Name: OEMCertification: CE

Model Number: WRA-6320A+WUPBV220

Minimum Order Quantity:

Price: Negotiable
Packaging Details: Plywood Cases
Delivery Time: 15-60 Days
Payment Terms: L/C, T/T
Supply Ability: Based On Order



## **Product Specification**

Brand Name: OEM
Media: Water
Port Size: DN20
Control Way: On/off
Valve Material: Plastic

Name: 2 Motorized Ball ValveHighlight: electrically operated valve



## **Product Description**

### 2 Way Electric Actuator Ball Valve 3/4 inch Motorized Plastic PVC Ball Valve

#### **Surface Treatment**

We offer the following processes to choose:

- 1. Mechanical Polishing (MP) to improve brightness (gloss, matte)
- 2. Acid Cleaning for Anti-corrosion
- 3. Electrolysis Polish (EP) to improve surface smoothness
- 4. Custom Process: Bright Annealing treatment eliminate strees to improve toughness

#### Application

- 1. HVAC system
- 2. Water treatment system
- 3. Heating syste
- 4. Industrial equipments
- 5. Chemical process
- 6. Agricultural irrigation
- 7. Replacing solenoid valve, particularly when solenoid cannot work reliably .lt can be installed at any angle and direction, and can work in moist conditions.
- 8. Regular watering the flowers, Timing humidification, Air compressor drain at regular time.

#### Technical Parameter

Medium: cold/hot water, with 50% glycol Temperature of medium: 2°C...90°C

Adissable pressure:2.0Mpa Cable Length: 0.5m or 1.5m

Environment Temperature:-20~65 Celsius

Protect rank: IP54/IP55 Package Include: 1x ball valve 1x Actuator Motor 1x Instruction manual

#### **Product Detailed**

WRA-63.... A

AC230/110/24V, 50/60Hz, on/off

| CIZE   | DN15  | DN20  | DN25 |
|--------|-------|-------|------|
| SIZE   | 1/2"  | 3/4"  | 1"   |
| d      | 13    | 18    | 23   |
| DIN dl | 20    | 25    | 32   |
| JISdl  | 22    | 26    | 32   |
| ANSIdi | 21.34 | 26.67 | 33.4 |
| BSdl   | 21.2  | 26.6  | 33.4 |
| D      | 56    | 64    | 73   |
| DI     | 31    | 36    | 47   |
| L      | 120   | 128   | 144  |
| LI     | 23    | 25    | 28   |
| Н      | 95    | 101   | 133  |
| H3     | 29.5  | 33.5  | 39   |
| H4     | 28    | 30    | 34   |
| H5     | 151   | 153   | 159  |
| H6     | 166   | 168   | 174  |

| NO. | Part                   | Material       | QTY |
|-----|------------------------|----------------|-----|
|     |                        |                |     |
| 1   | Body                   | U-PVC,C-PVC,PP | 1   |
| 2   | Ball                   | U-PVC,C-PVC,PP | 1   |
| 3   | Carrier O-Ring         | EPDM,FPM       | 1   |
| 4   | Seal Carrier           | U-PVC,C-PVC,PP | 1   |
| 5   | Union                  | U-PVC,C-PVC,PP | 2   |
| 6   | End Connector          | U-PVC,C-PVC,PP | 2   |
| 7   | Seal Seat              | PTFE           | 2   |
| 8   | Dampener Seal          | EPDM,FPM       | 2   |
| 9   | End Connestor O-Ring   | EPDM,FPM       | 2   |
| 10  | Stem O-Ring            | EPDM,FPM       | 2   |
| 11  | Stem                   | U-PVC,C-PVC,PP | 1   |
| 14  | Mounting Clamp         | PVC-M,SUS304   | 1   |
| 15  | Actuator Coupling Bush | PVC-M,SUS304   | 1   |
| 16  | Bolt                   | SUS 304        | 4   |



17733330123

miclecleanmo@gmail.com

watercontrol-valve.com

18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.