



## 3/4 Inch 2 Way Electric Water Ball Valve For Agricultural Irrigation

Our Product Introduction

for more products please visit us on [watercontrol-valve.com](http://watercontrol-valve.com)

### Basic Information

- Place of Origin: China
- Brand Name: OEM
- Certification: CE
- Model Number: WRA-6320A+WUPBV220
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: Plywood Cases
- Delivery Time: 15-60 Days
- Payment Terms: L/C, T/T
- Supply Ability: Based On Order



### Product Specification

- Application: General, Water Treatment System, Industrial Equipment, Agricultural Irrigation
- Temperature Of Media: Medium Temperature
- Power: Electric
- Media: Water
- Port Size: DN20 (3/4")
- Structure: Ball
- Product Name: Motorized Plastic PVC Ball Valve
- Control Type: ON/OFF
- Valve Type: 2 WAY
- Valve Material: Plastic
- Voltage: 220VAC+/-15%
- Open/Close Time: 16S/50Hz/12S/60Hz
- Warranty: 18 Month
- Package Type: Package Include: 1x Ball Valve 1x Actuator Motor 4x Instruction Manual



### More Images



wiring diagram



## Product Description

### 2 Way Electric Actuator Ball Valve 3/4 inch PVC Valves Water Control Motorized Plastic PVC Ball Valve

#### How do we control the quality of machining

1. High-precision CNC lathe processing parts.
2. Advanced Milling Machines
3. UT Inspection to ensure welding quality
4. Weld Polishing
5. 100% Appearance & Size Inspection online (thickness, roundness, etc.)
6. Size & Appearance Shaping

#### Technical Parameter

Medium: cold/hot water, with 50% glycol  
Temperature of medium: 2°C...90°C  
Adissable pressure:2.0Mpa  
Cable Length: 0.5m or 1.5m  
Environment Temperature:-20~65 Celsius  
Protect rank: IP54/IP55  
Package Include:  
1x ball valve  
1x Actuator Motor  
1x Instruction manual

#### Application

1. HVAC system
2. Water treatment system
3. Heating syste
4. Industrial equipments
5. Chemical process
6. Agricultural irrigation
7. Replacing solenoid valve, particularly when solenoid cannot work reliably .It can be installed at any angle and direction,and can work in moist conditions.
8. Regular watering the flowers, Timing humidification ,Air compressor drain at regular time.

#### Product Detailed

WRA-63.... A  
AC230/110/24V, 50/60Hz, on/off



## wiring diagram

SIZE	DN15 1/2"	DN20 3/4"	DN25 1"		
d	13	18	23		
DIN dl	20	25	32		
JISdl	22	26	32		
ANSIdl	21.34	26.67	33.4		
BSdl	21.2	26.6	33.4		
D	56	64	73		
DI	31	36	47		
L	120	128	144		
LI	23	25	28		
H	95	101	133		
H3	29.5	33.5	39		
H4	28	30	34		
H5	151	153	159		
H6	166	168	174		

NO.	Part	Material	QTY	
1	Body	U-PVC,C-PVC,PP	1	
2	Ball	U-PVC,C-PVC,PP	1	
3	Carrier O-Ring	EPDM,FPM	1	
4	Seal Carrier	U-PVC,C-PVC,PP	1	
5	Union	U-PVC,C-PVC,PP	2	
6	End Connector	U-PVC,C-PVC,PP	2	
7	Seal Seat	PTFE	2	
8	Dampener Seal	EPDM,FPM	2	
9	End Connector O-Ring	EPDM,FPM	2	
10	Stem O-Ring	EPDM,FPM	2	
11	Stem	U-PVC,C-PVC,PP	1	
14	Mounting Clamp	PVC-M,SUS304	1	
15	Actuator Coupling Bush	PVC-M,SUS304	1	
16	Bolt	SUS 304	4	





17733330123



miclecleanmo@gmail.com



watercontrol-valve.com

18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.