



Basic Information

Place of Origin: ChinaBrand Name: OEMCertification: CE

Model Number: WRA-6320+WUPBV215

Minimum Order Quantity:

Price: Negotiable
Packaging Details: Plywood Cases
Delivery Time: 15-60 Days
Payment Terms: L/C, T/T
Supply Ability: Based On Order



Product Specification

Application: General, Water Treatment System, Industrial

Equipments, Agricultural Irrigation

Temperature Of Media: Medium Temperature

Media: Water
 Port Size: DN15 (1/2")

Structure: Ball

Product Name: Motorized Plastic PVC Ball Valve

Voltage: 220VAC+/-15%

Control Type: 3-pointValve Type: 2 WayValve Material: Plastic

• Open/Close Time: 16S/50Hz/12S/60Hz

• Waranty: 18 Month

Package Type: Package Include: 1x Ball Valve 1x Actuator

Motor 1x Instruction Manual

Haladalala.



More Images









Product Description

DN15 1/2 inch 2 Way 220VAC Electric Actuated PVC Plastic Motorized Ball Valve Water Control

Company Information

Our company is specialist in design and production of high quality water valve, and has grown to become one of the leading manufacturers for fluid control valve. We design and manufacture a wide range of fluid valve,, such as float control valve, trunnion ball valve, water pressure reducing valve, rotary airlock valve, sanitary butterfly valve, hydraulic check valve, sewage air release valve, etc. Our constant technical innovation combined with stringent quality control systems has enabled us to deliver high performance and outstanding value in industrial applications.

Product Description

Technical Parameter

Medium: cold/hot water, with 50% glycol Temperature of medium: 2°C...90°C Adissable pressure:2.0Mpa Cable Length: 0.5m or 1.5m

Environment Temperature:-20~65 Celsius

Protect rank: IP54/IP55 Package Include: 1x ball valve 1x Actuator Motor

1x Instruction manual

Application

- 1. HVAC system
- 2. Water treatment system
- 3. Heating syste
- 4. Industrial equipments
- 5. Chemical process
- 6. Agricultural irrigation
- 7. Replacing solenoid valve, particularly when solenoid cannot work reliably .lt can be installed at any angle and direction,and can work in moist conditions.
- 8. Regular watering the flowers, Timing humidification ,Air compressor drain at regular time.

Product Detailed

WRA-6320

AC230/110/24V, 50/60Hz, 3-point

SIZE	DN15	DN20	DN25
	1/2"	3/4"	1"
d	13	18	23
DIN dl	20	25	32
JISdl	22	26	32
ANSIdi	21.34	26.67	33.4
BSdl	21.2	26.6	33.4
D	56	64	73
DI	31	36	47
L	120	128	144
LI	23	25	28
Н	95	101	133
H3	29.5	33.5	39
H4	28	30	34
H5	151	153	159
H6	166	168	174

NO.	Part	Material	QTY		
1	Body	U-PVC,C-PVC,PP	1		
2	Ball	U-PVC,C-PVC,PP	1		
3	Carrier O-Ring	EPDM,FPM	1		
4	Seal Carrier	U-PVC,C-PVC,PP	1		
5	Union	U-PVC,C-PVC,PP	2		
6	End Connector	U-PVC,C-PVC,PP	2		
7	Seal Seat	PTFE	2		
8	Dampener Seal	EPDM,FPM	2		
9	End Connestor O-Ring	EPDM,FPM	2		
10	Stem O-Ring	EPDM,FPM	2		
11	Stem	U-PVC,C-PVC,PP	1		
14	Mounting Clamp	PVC-M,SUS304	1		
15	Actuator Coupling Bush	PVC-M,SUS304	1		
16	Bolt	SUS 304	4		



Beijing Silk Road Enterprise Management Services Co.,LTD

17733330123



18-2 JinFu East Rd. Ulks Village. Futian New district. Shenzhen. China.